# Joining instruction\*



Product identification F 8/2 E U03N / U0 Article number 20200007


**Product group** 

food conveyor belt

### **Endless joining**

Recommended joining Joining addition Length of fingers (or steps) Width of fingers double finger joining

105 mm 4,13 inch 55 mm 2,17 inch 20 mm 0,79 inch



# Joining material

Joining material conveying side Joining material running side Joining material inside Additional material release paper mat silicone pad PU foil no



heating plate top release paper mat

heating plate bottom



conveyor belt (conveying site up) PU foil conveyor belt (conveying site up) silicone pad

# Joining parameters

Heating temperature top Heating temperature bottom Heating time

Heating til Pressure Note 150 °C 302 °F 150 °C 302 °F

3 minutes 1 bar

use same material for edge demarcation

#### Alternative joining methods

Finger joining alternative Step joining Wedge joining Mechanical joining single finger joining yes on request yes G001 Alligator RS62

# Notes on installation

Loosely assemble the conveyor belt and then tighten until it works seamlessly with full band loading. With no less than an elongation at fitting of 0.3%.

Technical status: 01/24

\*mentioned parameters are based on experience in production of endless seamed belt with our tools. By using other tools the parameters can differ. Specifications subject to change without notice.

www.▼ ■ 5 GmbH.eu